







3xLOGIC VISIX Gen III Camera & Mount Matrix

VERSION 1.0 | MAY 2020



Simple. Scalable. Secure.

STANLEY[®]
Products & Solutions

	Bullet			Indoor Dome
Camera Image				
Release Date	6/1/20	6/1/20	6/1/20	8/17/20
STANLEY Part #	68619 22431C	68618 22430C	68609 22420C	68791 22544C
NEW Part #	VX-5M-B-RIAW	VX-5M20-B-RIAW	VX-5M4-MB-IW	VX-2M-ID-RIAW
Legacy Part #	VX-4V-B-RI-02 VX-4M-B-RIAWD	VX-4M20-B-RIAWD	VX-4S4-MB-I-02	VX-2V-MD-RIWH
Max Image Resolution	5MP - 2592(H) X 1944(V)	5MP - 2592(H) X 1944(V)	5MP - 2592(H) X 1944(V)	2MP - 1920(H) x 1080(V)
Motorized? / Lens	Yes/2.7 ~ 13.5mm, F1.4	Yes/6 ~ 50mm, F1.6	No/4.0mm F2.0	No/2.8-12mm F1.4
Horizontal Field of View	H: 31° ~ 85°	H: 45° ~ 7°	H: 81°	H: 35°~96°
Video Compression	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG
Frame Rate	30fps	30fps	30fps	30fps
IR Range	50m (164ft)	50m (164ft)	50m (164ft)	30m (98ft)
WDR	WDR - 120dB	WDR - 120dB	WDR - 120dB	WDR - 120dB
Audio Input/Output	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	N/A	1[1.0Vms, 3K ohm]/ 1 Terminal Block
Alarm Input/Output	1/1	1/1	N/A	1/1
SD Card Capacity	128GB	128GB	128GB	128GB
Operating Conditions	-40°C ~ 50°C (-40°F ~ 122°F)	-40°C ~ 50°C (-40°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)
Environmental Rating	IP67	IP67	IP67	
Impact Protection	IK9	IK9	N/A	
Power Supply	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3
Power Consumption	12V DC Max 9W PoE Max 10.5W	12V DC Max 9W PoE Max 10.5W	12V DC Max 6.2W PoE Max 7.9W	12V DC Max 8W PoE Max 10W
Warranty	4 years	4 years	4 years	4 years




*ONVIF, Profile-S Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

Outdoor Dome					
Camera Image					
Release Date	6/1/20			7/15/20	7/15/20
STANLEY Part #	68612 22424C			68613 22425C	68614 22426C
NEW Part #	VX-5M-OD-RIAW			VX-8M-OD-RIAW	VX-2M-OD-RIAW
Legacy Part #	VX-4V-OD-RI-02	VX-4M-OD3-RIAWD	VX-4V-ID-RIAWD	VX-8S-OD4-RIAWD	VX-2S-D4-RIA
Max Image Resolution	5MP - 2592(H) X 1944(V)			8MP - 3840(H)x2160(V)	2MP - 1920(H) x 1080(V)
Motorized? / Lens	Yes/2.7 ~ 13.5mm, F1.4			Yes/3.6mm-10mm, F1.5	Yes/2.8-12mm F1.4
Horizontal Field of View	H: 31° ~ 90°			H: 46° ~ 98°	H: 35° ~ 96°
Video Compression	H.264, H.265, MJPEG			H.264, H.265, MJPEG	H.264, H.265, MJPEG
Frame Rate	30fps			30fps	60fps
IR Range	30m (98ft)			30m (98ft)	30m (98ft)
WDR	WDR - 120dB			WDR - 120dB	WDR - 120dB
Audio Input/Output	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)			1[1.0Vms, 3K ohm]/1 Terminal Block	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)
Alarm Input/Output	1/1			1/1	1/1
SD Card Capacity	128GB			128GB	128GB
Operating Conditions	-30°C ~ 50°C (-22°F ~ 122°F)			-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)
Environmental Rating	IP67			IP67	IP67
Impact Protection	IK10			IK10	IK10
Power Supply	12V DC PoE IEEE 802.3af Class3			12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3
Power Consumption	12V DC Max7.4W PoE Max 8.7W			12V DC 9.3W PoE 11.6W	12V DC Max 7.5W PoE Max 9.5W
Warranty	4 years			4 years	4 years






*ONVIF, Profile-S Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	Outdoor Dome				
Camera Image					
Release Date	Available Now!			7/15/20	7/15/20
STANLEY Part #	68529 22365C			68608 22423C	68615 22427C
NEW Part #	VX-5M28-MD-IW			VX-5M4-MD-IW	VX-2M-OD-RIAWH
Legacy Part #	VX-4V28-OD-I-02	VX-4S28-MD-I-02	VX-4V28-MD-IAW-02	VX-4V4-MD-I-02	VX-2M-OD3-RIAH
Max Image Resolution	5MP - 2592(H) X 1944(V)			5MP - 2592(H) X 1944(V)	2MP - 1920(H) x 1080(V)
Motorized? / Lens	No/2.8 mm, F1.8			No/4.0mm, F2.0	Yes/2.7-12mm F1.4
Horizontal Field of View	H: 103°			H: 83°	H: 35°~96°
Video Compression	H.264, H.265, MJPEG			H.264, H.265, MJPEG	H.264, H.265, MJPEG
Frame Rate	30fps			30fps	30fps
IR Range	30m (98ft)			30m (98ft)	30m (98ft)
WDR	WDR - 120dB			WDR - 120dB	WDR - 120dB
Audio Input/Output	1 (Built in Mic)			1 (Built in Mic)	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)
Alarm Input/Output	N/A			N/A	1/1
SD Card Capacity	128GB			128GB	128GB
Operating Conditions	-30°C ~ 50°C (-22°F ~ 122°F)			-30°C ~ 50°C (-22°F ~ 122°F)	-40°C ~ 50°C (-40°F ~ 122°F)
Environmental Rating	IP67			IP67	IP68
Impact Protection	IK10			IK10	IK10
Power Supply	12V DC PoE IEEE 802.3af Class2			12V DC PoE IEEE 802.3af Class2	12V DC PoE IEEE 802.3af Class3
Power Consumption	12V DC Max 6W PoE Max 7.2W			12V DC Max 6W PoE Max 7.2W	12V DC Max 7.5W PoE Max 9.5W
Warranty	4 years			4 years	4 years

*ONVIF, Profile-S Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	360/180 Panoramic		PTZ	MultiSensor	SMBK
Camera Image					
Release Date	Available Now!	8/17/20	8/17/20		8/17/20
STANLEY Part #	68610 22421C	68611 22422C	68621 22433C	Coming Soon	68616 22428C
NEW Part #	VX-6M-360-IA-02	VX-8M-180-IAW	VX-2S-OP-30X-IAW	VX-2M-CPIR-IAW	VX-SMBK-B-IW
Legacy Part #	VX-6M-360-IA6	VX-8S-180-AWD	VX-2S-OP-30X	VX-2S-CPIR-W	VX-SMBK-B-01
Max Image Resolution	5MP - 2592(H) X 1944(V)	8MP - 3840(H) X 2160(V)	2MP - 1920(H) x 1080(V)	2MP - 1920(H) x 1080(V)	4MP 560(H) x 1440(V)
Motorized? / Lens	No/1.55mm, F2.5	No/2.3mm, F2.8	Yes/4.3 ~ 129 mm F1.6 ~ F4.7, 30X Zoom	No/2.8mm, F2.0	No/4.0mm, F2.0
Horizontal Field of View	H: 185°	H: 180	H: 2°~59°		H: 81°
Video Compression	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG
Frame Rate	30fps	30fps	30fps	30fps	20fps
IR Range	30m (98ft)	25m (82ft)	60m (197ft)	10m (32ft)	50m (164ft)
WDR	No	WDR - 120dB	WDR - 120dB		WDR - 120dB
Audio Input/Output	1 (Built in Mic)/1, 3.5mm	1[1.0Vms, 3K ohm, 3.5mm] /1 (3.5mm)	1[1.0Vms, 3K ohm]/ 1 Terminal Block	1 (Built in Mic)/1 (Speaker)	N/A
Alarm Input/Output	1/1	1/1	1/1	1/1	N/A
SD Card Capacity	128GB	128GB		128GB	128GB
Operating Conditions	-30°C ~ 50°C (-22°F ~ 122°F)	-20°C ~ 50°C () (-°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-20°C ~ 50°C (-4°F ~ 122°F)
Environmental Rating	IP66	IP67	IP66	N/A	IP67
Impact Protection	IK9	N/A	IK10	N/A	N/A
Power Supply	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	24V PoE+ IEEE 802.3at	12V DC ±10% PoE (802.3af)	PoE IEEE 802.3af Class3
Power Consumption	12V DC Max 7.5W PoE Max 8.7W	12V DC 9.3W PoE 11.6W	12V DC PoE+ IEEE 802.3at	TBD	12V DC Max 7.2W PoE Max 7.7W
Warranty	4 years	4 years	2 years	4 years	4 years

*ONVIF, Profile-S Compliant









*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	SMBK	HD Analog	Time of Flight	Full Body	
Camera Image					
Release Date	8/17/20	Available Now!	Available Now!	7/15/20	
STANLEY Part #	68617 22429C	68623 22435C	68624 22436C	68620 22432C	68622 22434C
NEW Part #	VX-SMBK-D-IW	VA-2MB-OD-RIWH-02	VA-2MD-OD-RIWH-02	VX-VTOF-OD-01	VX-2M-F-AW
Legacy Part #	VX-SMBK-D-01	VA-2MB-OD-RIWH	VA-2MD-OD-RIWH	VX-VSS-20	VX-4M-F-AWD
Max Image Resolution	4MP - 2688(H) x 1520(V)	1920(H) X 1080(V)	1920(H) X 1080(V)	320(H)x240(V)	2MP - 1920(H) x 1080(V)
Motorized? / Lens	No/4.0mm, F2.6	Yes/2.8 ~ 12mm, F1.4	Yes/2.8 ~ 12mm, F1.4	No/Monochrome (Infrared) Fixed Iris	N/A
Horizontal Field of View	H: 86°	H: 86°	H: 86°	92° x 67°	N/A
Video Compression	H.264, H.265, MJPEG	AHD/TVI/CVI/CVBS	AHD/TVI/CVI/CVBS	N/A	H.264, H.265, MJPEG
Frame Rate	20fps	30fps	30fps	10fps	30fps
IR Range	30m (98ft)	50m (164ft)	50m (164ft)	N/A	N/A
WDR	WDR -120dB	WDR - 120dB	WDR - 120dB	N/A	WDR - 120dB
Audio Input/Output	1 (Built in Mic)	N/A	N/A	N/A	1 (Built in Mic)/1
Alarm Input/Output	N/A	N/A/1	N/A /1	N/A	1/1
SD Card Capacity	128GB	N/A	N/A	N/A	128GB
Operating Conditions	-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-20°C - 50°C (32°F - 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)
Environmental Rating	IP66	IP66	IP66	IP66	N/A
Impact Protection	N/A	IK9	IK10	N/A	N/A
Power Supply	PoE IEEE 802.3af Class3	12V DC AC24V Dual Voltage	12V DC AC24V Dual Voltage	12V DC ±10% 60w Ultra PoE	12V DC POE IEEE 802.3af
Power Consumption	12V DC Max 5.2W PoE Max 7.6W	12V DC 6.0W 24V AC: 5.5W	12V DC 5.22W 24V AC 4.35W	Max 38W	12V DC Max 3.5W PoE Max 5.0W
Warranty	4 years	4 years	4 years	2 years	4 years









*ONVIF, Profile-S Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE





We offer many high quality mounts to complement and elevate your project install. You'll find the perfect accessory to complete your unique security deployment.

		Wall Mounts				Pendant Mounts			
									
		VX-WM-BW14	VX-WM-BW06	VX-WM-BW10	VX-WM-BW11	VX-WM-BW05	VX-PM-BC14	VX-PM-BC10	VX-PM-BC11
STANLEY Part #		68598 22408C	68795 22547C	68595 22405C	68591 22415C	68594 22404C	68600 22410C	68596 22406C	68590 22414C
3xLOGIC Part Number	VX-2M-F-AW (None)								
	VX-5M-B-RIAW								
	VX-5M20-B-RIAW								
	VX-5M4-MB-IW								
	VX-5M-OD-RIAW			✓				✓	
	VX-2M-OD-RIAWH					✓			
	VX-8M-OD-RIAW			✓				✓	
	VX-5M28-MD-IW				✓				✓
	VX-5M4-MD-IW				✓				✓
	VX-6M-360-IA-02			✓				✓	
	VA-2MB-OD-RIWH-02								
	VA-2MD-OD-RIWH-02					✓			
	VX-VTOF-OD-01								
	VX-2M-ID-RIAW		✓						
	VX-2M-OD-RIAW			✓				✓	
	VX-8M-180-IAW								
	VX-2S-OP-30X-IAW	✓					✓		
	VX-2M-CPIR-IAW								
	VX-SMBK-B-IW								
	VX-SMBK-D-IW								

We offer many high quality mounts to complement and elevate your project install. You'll find the perfect accessory to complete your unique security deployment.

		Pendant Mounts	Pole Mounts		Junction Box Mounts			Gang Plate	
									
		VX-PM-BC07	VX-POLE-BP04	VX-POLE-BP07	VX-JB-BJC07	VX-JB-BJC03	VX-JB-BJC04	VX-JB-BJC02	VX-GP-01
STANLEY Part #		68597 22407C	68592 22402C	68602 22412C	68792 22545C	68599 22409C	68606 22418C	68607 22419C	68601 22411C
3xLOGIC Part Number	VX-2M-F-AW (None)								
	VX-5M-B-RIAW			✓	✓				
	VX-5M20-B-RIAW			✓	✓				
	VX-5M4-MB-IW			✓	✓				
	VX-5M-OD-RIAW		✓			✓			
	VX-2M-OD-RIAWH	✓	✓						
	VX-8M-OD-RIAW		✓			✓			
	VX-5M28-MD-IW		✓				✓		✓
	VX-5M4-MD-IW		✓				✓		✓
	VX-6M-360-IA-02		✓			✓			
	VA-2MB-OD-RIWH-02			✓	✓				
	VA-2MD-OD-RIWH-02	✓	✓					✓	
	VX-VTOF-OD-01								
	VX-2M-ID-RIAW								
	VX-2M-OD-RIAW		✓			✓			
	VX-8M-180-IAW			✓	✓				
	VX-2S-OP-30X-IAW		✓						
	VX-2M-CPIR-IAW								
	VX-SMBK-B-IW			✓	✓				
VX-SMBK-D-IW									

We offer many high quality mounts to complement and elevate your project install. You'll find the perfect accessory to complete your unique security deployment.

	In Ceiling Flush	Corner Mount	Pan/Tilt Bracket	Mount Is Included
				
	VX-FM-BR05	VX-FM-BR08	VX-CM-BC04	VX-VTOF-BTP
	68605 22417C	68604 22416C	68593 22403C	68794 22546C
STANLEY Part #				
VX-2M-F-AW (None)				
VX-5M-B-RIAW				
VX-5M20-B-RIAW				
VX-5M4-MB-IW				
VX-5M-OD-RIAW			✓	
VX-2M-OD-RIAWH	✓		✓	
VX-8M-OD-RIAW			✓	
VX-5M28-MD-IW			✓	
VX-5M4-MD-IW			✓	
VX-6M-360-IA-02			✓	
VA-2MB-OD-RIWH-02				
VA-2MD-OD-RIWH-02			✓	
VX-VTOF-OD-01				✓
VX-2M-ID-RIAW				
VX-2M-OD-RIAW			✓	
VX-8M-180-IAW				
VX-2S-OP-30X-IAW		✓	✓	
VX-2M-CPIR-IAW				✓
VX-SMBK-B-IW				
VX-SMBK-D-IW				

3xLOGIC Part Number

3xLOGIC

3xLOGIC Inc. has been a leading innovator in security technology for 15+ years. The company is recognized for providing easy-to-use surveillance and business intelligence solutions that seamlessly integrate video, access control, alarm audio and video verification, and disparate data sets such as ATM, Point-of-Sale, analytics, and more.

ONLINE COURSES

Can't dedicate a specific date or time to a course? We've got you covered. We're now offering On Demand on-line courses that can be completed as your schedule allows. Certification, Re-Certification and End User Courses are provided.

Visit www.3xLOGIC.com to see a description of current course offerings.

NEED SUPPORT?

For support related issues please email helpdesk@3xlogic.com or call us at (877) 395-6442 or +1 (303) 430-1969.