



3xLOGIC


3xLOGIC VISIX Gen III Camera Matrix

SEPTEMBER 2021






Simple. Scalable. Secure.

	Bullet			
Camera Image				
Release Date				
Part Number	VX-5M-B-RIAW	VX-5M20-B-RIAW	VX-5M20-B-RIAL	VX-5M4-MB-IW
Max Image Resolution	5MP - 2592(H) X 1944(V)	5MP - 2592(H) X 1944(V)	5MP - 2592(H) X 1944(V)	5MP - 2592(H) X 1944(V)
Motorized? / Lens	Yes/2.7 ~ 13.5mm, F1.4	Yes/6 ~ 50mm, F1.6	Yes/6 ~ 50mm, F1.6	No/4.0mm F2.0
Horizontal Field of View	H: 31° ~ 85°	H: 45° ~ 7°	H: 45° ~ 7°	H: 81°
Video Compression	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG
Frame Rate	30fps	30fps	30fps	30fps
IR Range	50m (164ft)	50m (164ft)	25m (80ft)	50m (164ft)
WDR	WDR - 120dB	WDR - 120dB	WDR - N/A	WDR - 120dB
Audio Input/Output	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	N/A
Alarm Input/Output	1/1	1/1	1/1	N/A
SD Card Capacity	256GB	256GB	256GB	256GB
Operating Conditions	-40°C ~ 50°C (-40°F ~ 122°F)	-40°C ~ 50°C (-40°F ~ 122°F)	-40°C ~ 50°C (-40°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)
Ratings	IP67 / IK9	IP67 / IK9	IP67 / IK9	IP67 / N/A
Edge Capability	Advanced Analytics or All-In-One	Advanced Analytics or All-In-One	Advanced Analytics or All-In-One	Advanced Analytics or All-In-One
Power Supply	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3
Power Consumption	12V DC Max 9W PoE Max 10.5W	12V DC Max 9W PoE Max 10.5W	12V DC Max 9W PoE Max 10.5W	12V DC Max 6.2W PoE Max 7.9W
Warranty	4 years	4 years	4 years	4 years

	Indoor Dome	Outdoor Dome			
Camera Image					
Release Date			VIGIL CLOUD		
Part Number	VX-2M-ID-RIAW	VX-4V-OD-RI-02	VX-5M-OD-RIAW	VX-4V-ID-RIAWD	VX-8M-OD-RIAW
Max Image Resolution	2MP - 1920(H) x 1080(V)		5MP - 2592(H) X 1944(V)		8MP - 3840(H)x2160(V)
Motorized? / Lens	Yes/2.8-12mm F1.4		Yes/2.7 ~ 13.5mm, F1.4		Yes/3.6mm-10mm, F1.5
Horizontal Field of View	H: 35°~96°		H: 31° ~ 90°		H: 46° ~ 98°
Video Compression	H.264, H.265, MJPEG		H.264, H.265, MJPEG		H.264, H.265, MJPEG
Frame Rate	30fps		30fps		30fps
IR Range	30m (98ft)		30m (98ft)		30m (98ft)
WDR	WDR - 120dB		WDR - 120dB		WDR - 120dB
Audio Input/Output	1[1.0Vms, 3K ohm]/ 1 Terminal Block		1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)		1[1.0Vms, 3K ohm]/1 Terminal Block
Alarm Input/Output	1/1		1/1		1/1
SD Card Capacity	256GB		256GB		256GB
Operating Conditions	-30°C ~ 50°C (-22°F ~ 122°F)		-30°C ~ 50°C (-22°F ~ 122°F)		-30°C ~ 50°C (-22°F ~ 122°F)
Ratings	N/A		IP67 / IK10		IP67 / IK10
Edge Capability	Advanced Analytics		Advanced Analytics or All-In-One		Advanced Analytics
Power Supply	12V DC PoE IEEE 802.3af Class3		12V DC PoE IEEE 802.3af Class3		12V DC PoE IEEE 802.3af Class3
Power Consumption	12V DC Max 8W PoE Max 10W		12V DC Max7.4W PoE Max 8.7W		12V DC 9.3W PoE 11.6W
Warranty	4 years		4 years		4 years






*ONVIF, Profile-S Compliant | All Cameras and Sensors are NDAA Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	Outdoor Dome				
Camera Image					
Release Date			VIGIL CLOUD		VIGIL CLOUD
Part Number	VX-2M-OD-RIAW	VX-4V28-OD-I-02	VX-5M28-MD-IAW	VX-4V28-MD-IAW-02	VX-5M4-MD-IAW
Max Image Resolution	2MP - 1920(H) x 1080(V)		5MP - 2592(H) X 1944(V)		5MP - 2592(H) X 1944(V)
Motorized? / Lens	Yes/2.8-12mm F1.4		No/2.8 mm, F1.8		No/4.0mm, F2.0
Horizontal Field of View	H: 35° ~ 96°		H: 103°		H: 83°
Video Compression	H.264, H.265, MJPEG		H.264, H.265, MJPEG		H.264, H.265, MJPEG
Frame Rate	60fps		30fps		30fps
IR Range	30m (98ft)		30m (98ft)		30m (98ft)
WDR	WDR - 120dB		WDR - 120dB		WDR - 120dB
Audio Input/Output	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)		1 (Built in Mic)/1 (3.5mm)		1 (Built in Mic)/1 (3.5mm)
Alarm Input/Output	1/1		1/1		1/1
SD Card Capacity	256GB		256GB		256GB
Operating Conditions	-30°C ~ 50°C (-22°F ~ 122°F)		-30°C ~ 50°C (-22°F ~ 122°F)		-30°C ~ 50°C (-22°F ~ 122°F)
Ratings	IP67 / IK10		IP67 / IK10		IP67 / IK10
Edge Capability	Advanced Analytics		Advanced Analytics or All-In-One		Advanced Analytics or All-In-One
Power Supply	12V DC PoE IEEE 802.3af Class3		12V DC PoE IEEE 802.3af Class2		12V DC PoE IEEE 802.3af Class2
Power Consumption	12V DC Max 7.5W PoE Max 9.5W		12V DC Max 6W PoE Max 7.2W		12V DC Max 6W PoE Max 7.2W
Warranty	4 years		4 years		4 years

*ONVIF, Profile-S Compliant | All Cameras and Sensors are NDAA Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	Outdoor Dome	360/180 Panoramic		PTZ	MultiSensor
Camera Image					
Release Date					
Part Number	VX-2M-OD-RIAWH	VX-6M-360-IAW	VX-8M-180-IAW	VX-2S-OP-30X-IAW	VX-2M-CPIR-IAW
Max Image Resolution	2MP - 1920(H) x 1080(V)	5MP - 2592(H) X 1944(V)	8MP - 3840(H) X 2160(V)	2MP - 1920(H) x 1080(V)	2MP - 1920(H) x 1080(V)
Motorized? / Lens	Yes/2.7-12mm F1.4	No/1.55mm, F2.5	No/2.3mm, F2.8	Yes/4.3 ~ 129 mm F1.6 ~ F4.7, 30X Zoom	No/2.8mm, F2.0
Horizontal Field of View	H: 35°~96°	H: 185°	H: 180	H: 2°~59°	—————
Video Compression	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG	H.264, H.265, MJPEG
Frame Rate	30fps	30fps	30fps	30fps	30fps
IR Range	30m (98ft)	30m (98ft)	25m (82ft)	60m (197ft)	10m (32ft)
WDR	WDR - 120dB	WDR - 120dB	WDR - 120dB	WDR - 120dB	—————
Audio Input/Output	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	1 (Built in Mic)/1, (3.5mm)	1[1.0Vms, 3K ohm, 3.5mm]/ 1 (3.5mm)	1[1.0Vms, 3K ohm]/ 1 Terminal Block	1 (Built in Mic)/1 (Speaker)
Alarm Input/Output	1/1	1/1	1/1	1/1	2/2
SD Card Capacity	256GB	256GB	256GB	256GB	256GB
Operating Conditions	-40°C ~ 50°C (-40°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-20°C ~ 50°C () (-°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)
Ratings	IP68 / IK10	IP66 / IK9	IP67 / N/A	IP66 / IK10	N/A
Edge Capability	Advanced Analytics	Advanced Analytics or All-In-One	Advanced Analytics	Advanced Analytics	All-In-One
Power Supply	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	12V DC PoE IEEE 802.3af Class3	24V PoE+ IEEE 802.3at	12V DC ±10% PoE (802.3af)
Power Consumption	12V DC Max 7.5W PoE Max 9.5W	12V DC Max 7.5W PoE Max 8.7W	12V DC 9.3W PoE 11.6W	12V DC PoE+ IEEE 802.3at	TBD
Warranty	4 years	4 years	4 years	2 years	4 years


*ONVIF, Profile-S Compliant | All Cameras and Sensors are NDAA Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	SMBK		HD Analog		Time of Flight
Camera Image					
Release Date					
Part Number	VX-SMBK-B-IW	VX-SMBK-D-IW	VA-2MB-OD-RIWH-02	VA-2MD-OD-RIWH-02	VX-VTOF-OD-01
Max Image Resolution	4MP 2560(H) x 1440(V)	4MP - 2560(H) x 1440(V)	1920(H) X 1080(V)	1920(H) X 1080(V)	320(H)x240(V)
Motorized? / Lens	No/4.0mm, F2.0	No/4.0mm, F2.0	Yes/2.8 ~ 12mm, F1.4	Yes/2.8 ~ 12mm, F1.4	No/Monochrome (Infrared) Fixed Iris
Horizontal Field of View	H: 81°	H: 82.3°	H: 86°	H: 86°	92° x 67°
Video Compression	H.264, H.265, MJPEG	H.264, H.265, MJPEG	AHD/TVI/CVI/CVBS	AHD/TVI/CVI/CVBS	N/A
Frame Rate	20fps	20fps	30fps	30fps	10fps
IR Range	50m (164ft)	30m (98ft)	50m (164ft)	50m (164ft)	N/A
WDR	WDR - 120dB	WDR - 120dB	WDR - 120dB	WDR - 120dB	N/A
Audio Input/Output	N/A	1 (Built in Mic)	N/A	N/A	N/A
Alarm Input/Output	N/A	N/A	N/A/1	N/A /1	1/1
SD Card Capacity	N/A	N/A	N/A	N/A	N/A
Operating Conditions	-20°C ~ 50°C (-4°F ~ 122°F)	-20°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)	-20°C - 50°C (32°F - 122°F)
Ratings	IP67 / N/A	IP66 / N/A	IP66 / IK9	IP66 / IK10	IP66 / N/A
Edge Capability	————	————	————	————	Advanced Analytics
Power Supply	PoE-IEEE 802.3af Class3	PoE IEEE 802.3af Class3	12V DC AC24V Dual Voltage	12V DC AC24V Dual Voltage	12V DC ±10% 60w Ultra PoE
Power Consumption	12V DC Max 7.2W PoE Max 7.7W	12V DC Max 5.2W PoE Max 7.6W	12V DC 6.0W 24V AC: 5.5W	12V DC 5.22W 24V AC 4.35W	Max 38W
Warranty	4 years	4 years	4 years	4 years	2 years

*ONVIF, Profile-S Compliant | All Cameras and Sensors are NDAA Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

	Thermals	
Camera Image		
Release Date		
Part Number	VX-VT-36	VX-VT-56
Max Image Resolution	206(H) x 156(V)	320(H) x 240(V)
Motorized? / Lens	No/4.0mm	No/4.0mm
Horizontal Field of View	36°	56°
Video Compression	H.264, MJPEG	H.264, MJPEG
Frame Rate	9fps	9fps
Range	36 - D: 76m, R: 46m, I: 15m	D: 76m, R: 46m, I: 15m
WDR	N/A	N/A
Audio Input/Output	1/1	1/1
Alarm Input/Output	1/2	1/2
SD Card Capacity	128GB	128GB
Operating Conditions	-40°C ~ 59°C (-40°F ~ 138°F)	
Ratings	IP66	IP66
Edge Capability	Advanced Analytics and All-In-One	Advanced Analytics and All-In-One
Power Supply	12V DC POE IEEE 802.3af	12V DC POE IEEE 802.3af
Power Consumption	12V DC Max 8.6W	12V DC Max 8.6W
Warranty	3 years	3 years

*ONVIF, Profile-S Compliant | All Cameras and Sensors are NDAA Compliant

*Certifications For All Cameras: FCC Part 15, Subpart B, Class A, CAN ICES-3 (A)/NMB-3(A) UL and ULC Safety CE

3xLOGIC

3xLOGIC Inc. has been a leading innovator in security technology for 15+ years. The company is recognized for providing easy-to-use surveillance and business intelligence solutions that seamlessly integrate video, access control, alarm audio and video verification, and disparate data sets such as ATM, Point-of-Sale, analytics, and more.

We are a global company with headquarters in Indiana, USA and Stockport, UK.

United States Office

11899 Exit 5 Parkway, Suite 100

Fishers, IN 46037

+1 (877) 3xLOGIC or +1 (877) 395-6442

sales@3xlogic.com

UK & Europe Office

1 Park Gate Close,

Bredbury, Stockport,

Cheshire,

SK6 2SZ,

UK

+44 (0)161 406 3400

sales@3xlogic.com

ONLINE COURSES

Can't dedicate a specific date or time to a course? We've got you covered.



We're now offering On Demand on-line courses that can be completed as your schedule allows. Certification, Re-Certification and End User Courses are provided.

Visit 3xLOGIC.com to see a description of current course offerings.

NEED SUPPORT?

For support related issues please email helpdesk@3xlogic.com or call one of our direct lines.

US Phone Number: (877) 395-6442

UK & Europe Phone Number: +44 (0)161 406 3400